

## Products / Cross bar to support floodlights






Cross bar for floodlights are made from 'U' section bar S235JRH steel, with a connecting pipe for post top installation.

Hot dip galvanized according to UNI EN ISO 1461 and supplied with 6 fixing screws M10.

### CROSS BAR FOR STEPPED POLES

#### Dimensions:

			FLOODLIGHTS SUGGESTED	
<b>TYPE</b>	mm	mm	N. max	kg
<b>SP05</b>	500	60	1	5
<b>SP10</b>	1000	60	2	9
<b>SP15</b>	1500	60	2/3	13
<b>SP20</b>	2000	60	3/4	17

### CROSS BAR FOR CONICAL-OCTAGONAL POLES

#### Dimensions:

			FLOODLIGHTS SUGGESTED	
<b>TYPE</b>	mm	mm	N. max	kg
<b>SPC05</b>	500	70	1	5
<b>SPC10</b>	1000	70	2	9

<b>SPC15</b>	1500	70	2/3	13
<b>SPC20</b>	2000	70	3/4	17

### CROSS BAR FOR POLIGONAL POLES POT

Dimensions:

			<b>FLOODLIGHTS SUGGESTED</b>	
<b>TYPE</b>	mm	mm	N. max	kg
<b>SP11</b>	1000	102	2	10
<b>SP18</b>	1500	102	2/3	14
<b>SP21</b>	2000	102	2/4	18

### CROSS BAR FOR STEPPED POLE R13

Dimensions:

			<b>FLOODLIGHTS SUGGESTED</b>	
<b>TYPE</b>	mm	mm	N. max	kg
<b>SP11/1</b>	1000	114	2	11
<b>SP18/1</b>	1500	114	2/3	15
<b>SP21/1</b>	2000	114	2/4	19

### CROSS BAR FOR POLIGONAL POLES POL




Dimensions:

			<b>FLOODLIGHTS SUGGESTED</b>	
<b>TYPE</b>	mm	mm	N. max	kg
<b>SP11/2</b>	1000	133	2	12
<b>SP18/2</b>	1500	133	2/3	16
<b>SP21/2</b>	2000	133	2/4	20

### CIRCULAR HEADFRAMES TO SUPPORT FLOODLIGHTS

Circular headframes are made from 'L' section bar S235JRH steel, which is curved to create a ring, with a centred connecting pipe for post top installation. Hot dip galvanized according to UNI EN ISO 1461 and supplied with 6 fixing screws M10.

**Dimensions:**

			<b>FLOODLIGHTS SUGGESTED</b>	
<b>TYPE</b>	mm	mm	N. max	kg
<b>SC60</b>	600	102	4	18
<b>SC61</b>	600	114	4	18
<b>SC62</b>	600	133	4	19
<b>SC120</b>	1200	102	6	35
<b>SC121</b>	1200	114	6	35
<b>SC122</b>	1200	133	6	36

**N.C.M. S.r.l. - Poles and high masts for lighting**