






Fiberglass rod selector

 <p>Profi-Set inclusive accessories</p> <p>Standard-Set without accessories</p> <p>BEGINNING RUNPOTEC RUNPOGLIDER with swivel and patented pressed flexible head with a bigger eyelet on top Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread, screwed to strand</p> <p>ENDING Ending joint with RUNPOTEC RTG Ø 6 mm thread</p> <p>INCL. ACCESSORIES</p>	<p>∅</p>	<p>Length</p>	<p>Tube diameter</p> 	<p>Bending radius</p> 	<p>Tension loads</p> 
	<p>∅ 4,5 mm</p>	<p>30 m 40 m 50 m 60 m 80m</p>	<p>30-80 mm</p>	<p>120 mm</p>	<p>1300 kg</p>
 <p>Automatic run-out brake</p> <p>Quick run with mounted rollers</p> <p>MECHANICAL METER COUNTER with hardened counter wheel</p> <p>BEGINNING: Schakle, stainless steel, with RUNPOTEC RTG Ø12 mm thread, screwed to strand</p> <p>ENDING: ENDING JOINT, STAINLESS STEEL, WITH RUNPOTEC RTG Ø12 MM THREAD</p>	<p>∅ 6 mm</p>	<p>40 m 50 m 60 m 80 m</p>	<p>40-100 mm</p>	<p>168 mm</p>	<p>2200 kg</p>
	<p>∅ 7,5 mm</p>	<p>40 m 50 m 60 m 80 m 100 m 120 m</p>	<p>50-120 mm</p>	<p>500 mm</p>	<p>3400 kg</p>
	<p>∅ 9 mm</p>	<p>40 m 50 m 60 m 80 m 100 m 120 m 150 m</p>	<p>60-200 mm</p>	<p>620 mm</p>	<p>4500 kg</p>
	<p>∅ 11 mm</p>	<p>100 m 120 m 150 m 200 m 250 m 300 m</p>	<p>80-250 mm</p>	<p>770 mm</p>	<p>6200 kg</p>
	<p>∅ 15 mm</p>	<p>150 m 200 m 250 m 300 m 350 m 400 m</p>	<p>180-450 mm</p>	<p>1200 mm</p>	<p>14500 kg</p>